

AIRONE 200 N/300 NEW

Hoists with telescopic arm – capacity 200–300 kg

ET 300 N

Stand hoist capacity 300 kg

Airone 200 N/300 New Standard Equipment

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Prearrangement for all IMER supports (gantry excluded) on Airone 200 N
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1.5-m pendant control
- ✓ Self-braking motor with magnetic device

Optional Accessories for Airone 300 New

- ✓ Prop
- ✓ Ballast container

Applications

The special machine configuration makes it easy to install thanks to better weight distribution for the operator. The raised loading point simplifies the passing of materials through windows. Airone 200 N and Airone 300 New have an extensible arm up to 1100 mm. Maximum capacity remains unchanged for the entire extension so bulky material can be lifted without the risk of striking the structures.

ET 300 N Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor
- ✓ IP67 plug
- ✓ Frame with 4 aluminium wheels
- ✓ Upper limit safety device
- ✓ Direct controls with 3-pushbutton 1.5-m pendant control
- ✓ Positioning brake
- ✓ Self-braking motor with magnetic device

Applications

It ensures maximum reliability and durability. The gearmotor is built with helical-toothed steel gears in oil bath.



Airone 200 N

Column prop for Airone 300 New

The Airone 300 New has the possibility of a specific optional column prop for hoists with max. capacity of 300 kg.



Airone 300 New



ET 300 N

		AIRONE 200 N	AIRONE 300 New	ET 300 N
Maximum capacity	kg	200	300	300
Av. full load lifting speed	m/min	19	19	19/18
Max. working height	m	30	30	30
Ø steel rope	mm	5	5	5
Rope length	m	31	31	31
Motor power rate 230V/50Hz	kW	0.75	1.1	1.1
Motor speed	rpm	1380	1320	1320
Running current	A	7.5	10	12
Machine weight	kg	45	55	50
SPL in operator's position	dB(A)	72	72	<75
Dimensions w/l/h	mm	350/820/550	350/820/550	330/780/380
Packing dimensions w/l/h	mm	330/850(1100)/625	330/850(1100)/625	350/820/440



Gantry for stand hoists