

Standard Equipment

- ✓ Electric safety limit switch
- ✓ Switch with IP 55 no-volt coil and IP 67 plug
- ✓ Placing handle
- N. 2 standard shatter-resistant poly drums suitable for low temperatures **LONG LIFE**
- ✓ N. 1 3-action paddle
- ✓ Packing: cardboard

Optional Accessories

- ✓ Residual current device kit (RCD)
- ✓ Kit with 5 drums LONG LIFE

115V/60Hz SPH 220V/60Hz SPH

MOTOR AVAILABLE


✓ Mix-ALL

NEW

Applications

Ideal for small building sites or refurbishment work.
Lightweight, compact and very quiet, it is suitable for professional
use. Specifically designed for mixing self-levelling material, fiber
reinforced material and concrete repair material.

Homogeneous and no trapped air perfect mixing.



NEW PADDLE 3-ZONE MIXING ACTION





		MIX-ALL
Drum capacity	I	56
Mixing performance	I	47
Drum diameter	mm	580
Paddle speed	rpm	55
Electric motor power rate 230V/50Hz	kW	0.55
Running current	А	5
SPL in operator's position	dB(A)	59
Machine weight (packing)	Kg	30 (32)
Dimensions w/l/h (packing)	mm	580/630/795 (585/620/455)