SMALL 50 EVO

Polyvalent eccentric screw pump, plastering / fillering machine

Small 50 ES EVO 230V/50Hz - 2,5 kW with vibrating grid and compressor 1106341

Small 50 EVO 230V/50Hz - 1,5 kW **1106342**

















Multi-accessory and adaptable to all mortar pumping needs.



Continuous speed variation and a series of pumping units provide a material flow from 0.3 to 14 l/min.

Description

Ultra-compact, light and powerful. Accessories allow the pumping or spraying of multiple products:

- Traditional lime / cement plasters
- Premixed / pre-dosed plasters based on cement and lime
- Premixed / pre-dosed structural plasters
- Premixed / pre-dosed restorative plasters
- Binders / mortars for consolidation injections
- Insulating plasters polystyrene or cork based
- Thixotropic fiber-reinforced reinforcement mortars
- Filling shotcrete
- Self-levelling cement / anhydride based screeds
- Mortars for grouts / stuccos
- All free-solvent paints
- Adhesives for thermal insulation coatings
- Smoothing plasters
- Smoothers for decorative finishing with silicates or minerals
- Waterproofing plasters, even fiber-reinforced
- Fireproofing plasters

Equipped with the exclusive IMER R2 inverter, which features a pumping speed variator and operating diagnostics, for total control of the conditions of use in complete safety.

It can be used in combination with any type of external mixer:

- Planetary mixer series "MIX"
- Continuous mixer series "SPIN"
- Concrete mixer series "SYNTESI", "MINIBETA" or "RIOBETA"

Operation

Small 50 EVO is usually positioned under the discharge outlet of a mixer to pour the mixture directly into the hopper.

Wet products that do not need to be mixed, can be poured directly into the hopper.

The mixture contained in the hopper is sucked by the rotor-stator pumping system and pushed into the pipe until it reaches the opposite end.

Accessories for spraying the products or devices for making injections at controlled pressure can be connected. Otherwise the machine can use a hose for the pouring of self-levelling or filling products.

Set the pumping speed using the exclusive IMER R2 inverter, adapting the machine to the different needs.

SMALL 50 EVO is equipped with a diagnostic display, which signals any anomalies during use and related resolution methods.

The exclusive IMER R2 inverter allows the SMALL 50 EVO can operate with appropriately sized generators.











250 mm oversized wheels and lifting handles for easy handling.



Useful toolbox.

Standard Equipment


otaniaa a Equipment
Stainless steel hopper
Stator and rotor D8 1.5 ECO
Power supply and control panel with inverter
20 m electric power cable
Electric remote control
Pressure measuring unit
Accessory box
Vibrating grid (Small 50 ES EVO)
Premixed / traditional mortar kit (Small 50 ES EVO)
Electric diaphragm compressor IM250 (Small 50 ES EVO)


Technical data SMALL 50 ES EVO

Supply	-	230V/50Hz	
Maximum installed power	kW	2.5	
Material flow rate*	l/min	0.8 to 14	
Max. pumpable grainsize*	mm	6	
Max. pumping distance Pipe Ø 19 mm*	m	15	
Max. pumping distance Pipe Ø 25 mm*	m	25	
Hopper capacity	I	50	
Loading height	mm	650	
Sound pressure level	dB (A)	< 74	
Dimensions width / length / h	mm	535/1199/796	
Machine weight	kg	69	
Compressor weight	kg	28	
Packed machine dimensions width / length / h	mm	550/1250/1100	
Packed machine weight	kg	120	


(*) The values indicated are subject to variations based on the characteristics of the materials used, their consistency, the type of stator / rotor installed and the size of the pipe used.

Small 50 ES EVO





Small 50 EVO





Standard setup **SMALL 50 ES EVO**



1106341

Small 50 ES EVO 230V/50Hz 2.5 kW

- → MRecommended for:
- Traditional lime / cement plasters
- Premixed / pre-dosed plasters based on cement and lime
- Premixed / pre-dosed structural plasters
- Premixed / pre-dosed restorative plasters
- Thixotropic fiber-reinforced mortars for reinforcement
- Insulating plasters based on polystyrene or cork
- Fillings shtocrete
- Fireproofing mortars
- Other accessories are applicable for specific uses..

Setups for specific applications **SMALL 50 EVO**



1106342

Small 50 EVO 230V/50Hz 1.5 kW **S1**

- Recommended setup for:
- Pressure-controlled consolidation injections

Maximum installed power 1.5 kW

1107006 Injection kit for R2 panel

1108005 Injection kit for A1 panel

- Pressure meter and pressure switch group
- Reduction M. 1 "F. 3/4" in brass
- Small 50 lance with 1 hose holder deflector Ø 16
- 10 m material holder hose Ø 25 with cam couplings
- 5 m material holder hose Ø 25 with cam couplings
- ullet 1 nozzle cleaner and 1 sponge Ø 30





1106342 Small 50 EVO 230V/50Hz 1.5 kW

S2

- → Recommended setup for:
- Adhesives for thermal insulation coatings
- Smoothing compounds for plaster
- Smoothers for decorative finishing with silicates or other minerals
- Waterproofing

Maximum installed power 3.7 kW

1107010 Smoothing and grouting kit

- Spray gur
- 1 set of deflectors Ø5-Ø6-Ø8-Ø12 mm
- 1 deflector with hose connection Ø16
- 10 + 5 m material holder hose \emptyset 25 with cam couplings
- \bullet 16 m air hose Ø 13 with Geka couplings
- \bullet 1 nozzle cleaner and 1 sponge Ø 30



1107610



Piston compressor C400 230V / 50Hz 2.2 kW

1107513



Hopper cover

1107084



Stator D 5-2.5 MONO CLAMP

- Color: purple
- Max. grain size 3 mm
- Flow rate (I / min) 0.6-10
- Pressure 25 bar

1107085



Rotor D 5-2.5 MONO

Setups for specific applications **SMALL 50 EVO**



1106342 Small 50 EVO 230V/50Hz 1.5 kW

S3

- Recommended setup for:
- Mortars for grouts / stuccos

Max. installed power 1.7 kW

1107499 —



Conical joint gun

- Sectionable steel tube to obtain the desired exit diameter
- Anti-spill valve

1107525



Material holder hose Ø 25 - 15 m with cam couplings

1107016

Internal vibrating hopper 220V / 50-60Hz

1107032



Stator D 4-1/2 CLAMP

- Color: lemon yellow
- Pressure (bar) 25
- Max. grain size (mm) 2
- Flow rate (I / min) 0.3-4.5

1107033



Rotor D 4-1/2



1106342 Small 50 EVO 230V/50Hz 1.5 kW

S4

- → Recommended setup for:
- Solvent-free paints

Maximum installed power 3.7 kW

1107009 Painting kit

- Spray gun + deflectors Ø5-Ø6
- 10 m material holder hose Ø 19 with cam couplings
- 16 m air hose Ø 13 with Geka couplings
- 1 nozzle cleaner and 1 sponge Ø 25
- Specific couplings for piping connection



1107610



C400 piston compressor 230V / 50Hz 2.2 kW

1107513

1107085



Hopper cover

1107084



Stator D 5-2.5 MONO CLAMP

- Color: purple
- Max. grain size 3 mm
- Flow rate (I / min) 0.6-10
- Pressure 25 bar

Rotor D 5-2.5 MONO

Kits and accessories for customized setups

SMALL 50 EVO / SMALL 50 ES EVO



- → Recommended setup for:
- Traditional lime / cement plasters
- Premixed / pre-dosed plasters based on cement and lime
- Premixed / pre-dosed structural plasters
- Premixed / pre-dosed restorative plasters
- Thixotropic fiber-reinforced mortars for reinforcement
- Insulating plasters based on polystyrene or cork
- Fire proofing mortars

Premixed / traditional mortar kit

- Spray gun
- Deflectors Ø 12 for conventional products
- **1107005** Deflectors Ø 10-14 for premixed products 15 m material holder hose Ø 25 with cam couplings

 - 16 m air hose Ø 13 with Geka couplings
 - 1 nozzle cleaner
 - 1 sponge Ø 30



- Recommended setup for:
- Mortars for grouts / stuccos
- Adhesives for thermal insulation coatings
- Smoothing plasters
- Smoothers for decorative finishing with silicates or minerals
- Waterproofing
- Solvent-free paints
- Deep groutings on stones
- Groutings on exposed stones

Smoothing and grouting kit

- Spray gun
- 1 set of deflectors Ø5-Ø6-Ø8-Ø12 mm
- **1107010** 1 deflector with hose connection \emptyset 16
 - 10 + 5 m material holder hose Ø 25 with cam couplings
 - 16 m air hose Ø 13 with Geka couplings
 - 1 nozzle cleaner and 1 sponge Ø 30



- → Recommended setup for:
- Binders / mortars for consolidation injections at controlled pressure

1107006 Injection kit for R2 panel

1108005 Injection kit for A1 panel

- Pressure control group with adjustable pressure switch 0.5-5 bar
- ullet Small 50 gun with 1 hose holder deflector Ø 16
- 10 m material holder hose Ø 25 with cam couplings
- 5 m material holder hose Ø 25 with cam couplings
- 1 nozzle cleaner and 1 sponge Ø 30



1107009 Painting kit

- Spray gun + deflectors Ø5-Ø6
- 10 m material holder hose Ø 19 with cam couplings
- 16 m air hose Ø 13 with Geka couplings
- 1 nozzle cleaner and 1 sponge Ø 25
- Specific couplings for piping connection

Accessories for customized setups **SMALL 50 EVO / SMALL 50 ES EVO**

Electric diaphragm compressor

Recommended for:

- Traditional lime / cement plasters
- Premixed / pre-dosed plasters based on cement and lime
- Premixed / pre-dosed structural plasters
- Premixed / pre-dosed restorative plasters
- Thixotropic fiber-reinforced mortars for reinforcement
- Insulating plasters based on polystyrene or cork
- Fireproofing mortars



Electric diaphragm compressor IM250 230V / 50Hz 250 I / min. 0.75 kW

Piston compressor

Recommended for:

- Adhesives for thermal insulation coatings
- Smoothing compounds for plaster
- Smoothers for decorative finishing with silicates or minerals
- Waterproofing, even fiber-reinforced

• Traditional products packed on site

• Solvent-free paints



Piston compressor C400 230V / 50Hz 2.2 kW

Vibrating grid

Recommended for:

1107510

1107543



Vibrating grid 230V / 50-60Hz 0.2 kW

Internal vibrating hopper Recommended for:

1107016 • Mortars for grouts / stuccos



Internal vibrating hopper 220V / 50-60Hz 0.2 kW

Hopper cover

→ Recommended for:

• Products' protection from the air during application

1107513



Hopper cover

1107515



Pressure control unit with adjustable pressure switch 0.2-5 bar for R2 panel



Pneumatic wheels kit

1108007

Pressure control unit with adjustable pressure switch 0.2-5 bar for A1 panel

1107512



Pressure gauge meter

1107544



Remote control extension 15 m for

R2 panel

1107103



Cleaning kit for DN25 pipes with air

1108009



1107519



10 pieces sponge kit for cleaning hose \emptyset 25

1107545



Remote control 16 m for R2 panel

1107520 Remote control 16 m for A1 panel

10 pieces sponge kit for cleaning hose Ø 35 (also hopper cap Small 50 EVO)

1108008

Accessories SMALL 50 EVO / SMALL 50 ES EVO

D8 - 1.5 Green

→ Recommended for:

- Traditional lime / cement plasters
- Premixed / pre-dosed plasters based on cement and lime
- Premixed / pre-dosed structural plasters
- Premixed / pre-dosed restorative plasters
- Thixotropic fiber-reinforced mortars for reinforcement
- Insulating plasters based on polystyrene or cork
- Fireproofing mortars

Pressure (bar) 15 Max. grain size (mm) 6



Stator D 8-1.5 MONO CLAMP

1107031



Rotor D 8-1.5 MONO

Flow rate (I / min) 0.8 -14

D5 - 2.5 Purple

Recommended for:

- Adhesives for thermal insulation coatings
- Smoothing compounds for plaster
- Skim coats for decorative finishing with silicates or minerals
- Waterproofing, even fiber-reinforced
- Solvent-free paints

1107084

D 5-2.5 MONO CLAMP

1107085

Rotor D 5-2.5 MONO

Pressure (bar) 25 Max. grain size (mm) 3 Flow rate (I / min) 0.6-10

D4 - 1/2 Lemon Yellow

Recommended for:

• Mortars for grouts / stuccos

Pressure (bar) 25 Max. grain size (mm) 3 Flow rate (I / min) 0.3-4.5



Stator D 4-1/2 CLAMP

1107033

Rotor D 4-1/2

1107540

Gun for premixed / traditional with deflector Ø 14

1107568

Spray gun Ø 25F with anti-spill valve and air flow regulator

1107549

Lightened fireproofing gun 1.43 m

1107011

Gun for smoothing / grouting / injections without deflectors

1107604



Deflector kit 5-6-8-12-16 tempered stainless steel

1107499



Conical joint gun

1107504 1108006



Joint gun R2 panel

Joint gun A1 panel with control sensor: On-Open / Off-Closed 24V socket

1107570



U bend steel hose Ø 25

Concrete hoses with camlock connections

1107529



Material holder hose Ø 19 - 10 m with cam couplings

Material holder hose Ø 25 - 15 m with cam couplings

Material holder hose Ø 25 - 10 m with cam couplings

Material holder hose Ø 25 - 5 m with cam couplings

Quick couplings compressed air hoses

1107530

1107531

Air hose Ø 13 - 5 m with Geka couplings

1107532

Air hose Ø 13 - 10 m with Geka couplings

Air hose Ø 13 - 16 m with Geka couplings

1107076

Air hose Ø 13 - 20 m with Geka couplings

1107527

Accessories **SMALL 50 EVO / SMALL 50 ES EVO**

				-		1
			1107540	1107011	1107549	1107568
1107551		10 pcs kit Deflectors Ø 10 in polyurethane for premixed plaster	\otimes		igoremsize	\bigcirc
1107552		10 pcs kit Deflectors Ø 12 in polyurethane for premixed plaster	\otimes		\otimes	\otimes
1107553		10 pcs kit Deflectors Ø 14 in polyurethane for premixed plaster	⊗		\otimes	\otimes
1107554		10 pcs kit Deflectors Ø 16 in polyurethane for premixed plaster	⊗		\otimes	\otimes
1107557		5 pcs kit Deflectors Ø 10 in polyurethane for traditional plaster	Ø			
1107558		5 pcs kit Deflectors Ø 12 in polyurethane for traditional plaster	\otimes			
1107559		5 pcs kit Deflectors Ø 14 in polyurethane for traditional plaster	Ø			
1107560		5 pcs kit Deflectors Ø 16 in polyurethane for traditional plaster	\otimes			
1107561		3 pcs kit Deflectors Ø 5 hardened steel for painting, smoothing, grouting		⊗		
1107562		3 pcs kit Deflectors Ø 6 hardened steel for painting, smoothing, grouting		⊗		
1107563		3 pcs kit Deflectors Ø 8 hardened steel for smoothing		⊗		
1107564		3 pcs kit Deflectors Ø 12 hardened steel for joints with compressor aid		Ø		
1107566		3 pcs kit Deflectors with hose nozzle Ø 16		⊗		